

3018WC • 18" Wine Captain® Model • Modular 3000 Series

FEATURES & BENEFITS

PERFORMANCE

INTERIOR/EXTERIOR

INTEGRATION



STAINLESS FRAME



INTEGRATED FRAME



STAINLESS FRAME (LOCK)



STAINLESS FRAME (HANDLELESS PANEL)*



INTEGRATED SOLID



STAINLESS SOLID (HANDLELESS PANEL)*

- Volume of 3.6 cu ft holds up to 31 wine bottles (750 ml)
- Temperature range: 38°F 65°F
- Convection cooling system rapidly and efficiently takes items to the set temperature
- U-Select[®] Control offers three distinct modes: Sparkling Wine: 38°F - 50°F, White Wine: 45°F - 55°F, Red Wine: 55°F - 65°F
- U-Select® Control with digital OLED display
- Rubber mounted compressor virtually eliminates vibration

• Black interior is illuminated with LED theater lighting that

automatically turns off when the door is closed, or can be set to stay on for 3, 6, or 24 hours Robust full-extension black vinyl coated wine racks allow for easy access and prevent bottles from shifting Wine racks accommodate a variety of bottle shapes and sizes; the fourth and fifth racks allow for larger diameter wine and

- champagne bottles
 LowE coated, argon gas filled triple thermopane glass door provides protection from harmful UV light
- Standard commercial stainless steel handle is interchangeable with professional handle accessory
- The door swing on non-lock models is field reversible, and is shipped right-hand hinged
- Lock models must be ordered right-hand or left-hand hinged
- Robust, concealed and covered hinges with built-in door stop and closer
- Adjustable grille can be shifted front-to-back and up-and down
- Integrated model requires 3/4" custom panel of your choice, or can accept U-Line Euro Style Handleless Stainless Panel Accessory (must be ordered separately)
- Grille can accept an integrated toe-kick
- Four independently adjustable leveling legs; rear legs are adjustable from the front for ease of installation

MODEL DETAILS

| Model | Voltage/Hz | Door Swing | Finish | Shipping Weight |
|-----------------|------------|-------------------|------------------------|-----------------|
| U-3018WCS-00B | 115 / 60 | Field Reversible | Stainless Frame | 134 lb |
| U-3018WCS-13B | 115 / 60 | Right-Hand Hinged | Stainless Frame (Lock) | 134 lb |
| U-3018WCS-15B | 115 / 60 | Left-Hand Hinged | Stainless Frame (Lock) | 134 lb |
| U-3018WCINT-00B | 115 / 60 | Field Reversible | Integrated Frame | 139 lb |
| U-3018WCINT-60B | 115 / 60 | Field Reversible | Integrated Solid | 133 lb |

ACCESSORIES

| Model | Description | Finish | Shipping Weight |
|-------------|---|-----------|-----------------|
| 80-54247-00 | Professional Door Handle, 1 1/4" Diameter | Stainless | 2 lb |
| 80-54214-00 | Commercial Door Handle, 7/8" Diameter | Stainless | 2 lb |
| U-ESPF45S* | Euro Style Handleless Panel, 18" Frame | Stainless | 6 lb |
| U-ESP45S* | Euro Style Handleless Panel, 18" Solid | Stainless | 9 lb |


^{*}Installs on integrated models.




Modular 3000 Series • 18" Wine Captain® Model • 3018WC

DIMENSIONS

Dimensions shown apply to all finishes, including Integrated (INT) models with 3/4" integrated panel/frame installed.



CABINET CUT-OUT



SPECIFICATIONS

| Model | 3018WC | |
|--------------------------------|--|--|
| Amps: Running | 1.2 | |
| Capacity: Volume (cu ft) | 3.6 | |
| Capacity: Wine Bottle (750 ml) | 31 | |
| Control Type | U-Select® | |
| Dimensions: Product Depth | 23 7/16" / 590 mm | |
| Dimensions: Product Height | 33 ¹¹ / ₁₆ " / 856 mm | |
| Dimensions: Product Width | 17 ³ / ₄ " / 450 mm | |
| ENERGY STAR | N/A | |
| Panel Height | 30" / 762 mm | |
| Panel Thickness | ³ / ₄ " / 20 mm | |
| Panel Type | 2 ³ / ₄ " / 70 mm Frame Panel or Solid Panel (-60 suffix) | |
| Panel Width | 17 5/8" / 445 mm | |
| Product Weight: Max | 125 lb | |
| Refrigerant Type | R600a | |
| Sabbath (Star K Certified) | Yes | |
| Temperature Range | 38°F - 65°F | |

INSTALLATION NOTES

When installing adjacent to wall, ensure 2 $^{1}\!\!/\!_{2}{''}$ clearance on hinged side for 90° door opening, allowing ample room for door handle.

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

COOLING SYSTEM





ELECTRICAL REQUIREMENTS

This unit requires a grounded, polarized 115 VAC, 60 Hz, 15 A power supply (normal household current).





Please visit U-Line.com to view this model's User Guide. All specifications are subject to change without notice.