T36IF905SP 36-INCH BUILT-IN FREEZER COLUMN WITH INTERNAL ICE MAKER



FREEDOM® COLLECTION, PANEL-READY











FEATURES & BENEFITS

- Full Stainless Steel Inner Liner
- Freedom® Hinge enables true flush design
- Auto Door Opening provides the opening of the door with just a slight push or pull
- Energy Efficient Diamond Ice made with twist tray technology
- Smooth Filtered Lighting for clear and easy viewing of all product
- SoftClose® Drawers for easy and controlled storage
- Sleek clean design for the perfect symmetry when paired with additional columns
- TFT control panel managing all your columns functions

TEMPERATURE RANGES	
Freezer	-11°F (-24°C) to 7°F (-14°C)
SuperFreeze®	-22°F (-30°C) for approximately 52 hours
Energy Saving (Economy) Mode	3°F (-16°C)

GENERAL PROPERTIES		
Home Connect™ (Wi-Fi Enabled)	Yes	
Panel Ready	Yes	
Reversible Door Swing	Yes	
SoftClose® Door	Yes*	
SoftClose® Drawers	Yes	
Lighting	LED Sidewall and Theater Lighting	
Freezer Shelves	4	
Adjustable Shelves	3	
Shelf Material	Glass w/Aluminum Profile	
Full Extension Drawers @ 115° Door Opening Angle	Yes	
General Use Drawer	2	
Door Bins	3	
External LED Proximity Sensor	No	
Oversized Dispenser Opening	No	
Chilled Water, Crushed and Cubed Ice	No	
Rapid Water Replenishment System	No	
Ice Maker with Diamond Ice System	Yes	
Door Open Alarm	Yes	
Open Door Assist	Yes	
	Sabbath, Economy, Vacation	
Special Modes		
Special Modes CAPACITY		
·		
CAPACITY	Vacation	
CAPACITY Total Capacity (cu. ft.)	Vacation	
CAPACITY Total Capacity (cu. ft.) PERFORMANCE	Vacation 19.4 cu. ft.	
CAPACITY Total Capacity (cu. ft.) PERFORMANCE Dedicated Evaporator & Compressor System	Vacation 19.4 cu. ft. Yes	
CAPACITY Total Capacity (cu. ft.) PERFORMANCE Dedicated Evaporator & Compressor System SuperFreeze®	Vacation 19.4 cu. ft. Yes Yes	
CAPACITY Total Capacity (cu. ft.) PERFORMANCE Dedicated Evaporator & Compressor System SuperFreeze® Defrost Process	Vacation 19.4 cu. ft. Yes Yes	
CAPACITY Total Capacity (cu. ft.) PERFORMANCE Dedicated Evaporator & Compressor System SuperFreeze® Defrost Process TECHNICAL DETAILS	Vacation 19.4 cu. ft. Yes Yes Frost-Free	
CAPACITY Total Capacity (cu. ft.) PERFORMANCE Dedicated Evaporator & Compressor System SuperFreeze® Defrost Process TECHNICAL DETAILS Watts (W)	Vacation 19.4 cu. ft. Yes Yes Frost-Free 350 W	
CAPACITY Total Capacity (cu. ft.) PERFORMANCE Dedicated Evaporator & Compressor System SuperFreeze® Defrost Process TECHNICAL DETAILS Watts (W) Current (A)	Yes Yes Frost-Free 350 W	
CAPACITY Total Capacity (cu. ft.) PERFORMANCE Dedicated Evaporator & Compressor System SuperFreeze® Defrost Process TECHNICAL DETAILS Watts (W) Current (A) Volts (V)	Vacation 19.4 cu. ft. Yes Yes Frost-Free 350 W 15 A 110-120 V	
CAPACITY Total Capacity (cu. ft.) PERFORMANCE Dedicated Evaporator & Compressor System SuperFreeze® Defrost Process TECHNICAL DETAILS Watts (W) Current (A) Volts (V) Frequency (Hz)	Vacation 19.4 cu. ft. Yes Yes Frost-Free 350 W 15 A 110-120 V 60 Hz	
CAPACITY Total Capacity (cu. ft.) PERFORMANCE Dedicated Evaporator & Compressor System SuperFreeze® Defrost Process TECHNICAL DETAILS Watts (W) Current (A) Volts (V) Frequency (Hz) Power Cord Length (in.)	Vacation 19.4 cu. ft. Yes Yes Frost-Free 350 W 15 A 110-120 V 60 Hz 118	
CAPACITY Total Capacity (cu. ft.) PERFORMANCE Dedicated Evaporator & Compressor System SuperFreeze® Defrost Process TECHNICAL DETAILS Watts (W) Current (A) Volts (V) Frequency (Hz) Power Cord Length (in.) Plug Type	Vacation 19.4 cu. ft. Yes Yes Frost-Free 350 W 15 A 110-120 V 60 Hz 118	
CAPACITY Total Capacity (cu. ft.) PERFORMANCE Dedicated Evaporator & Compressor System SuperFreeze® Defrost Process TECHNICAL DETAILS Watts (W) Current (A) Volts (V) Frequency (Hz) Power Cord Length (in.) Plug Type DIMENSIONS & WEIGHT	Vacation 19.4 cu. ft. Yes Yes Frost-Free 350 W 15 A 110-120 V 60 Hz 118 120V-3 Prong	
CAPACITY Total Capacity (cu. ft.) PERFORMANCE Dedicated Evaporator & Compressor System SuperFreeze® Defrost Process TECHNICAL DETAILS Watts (W) Current (A) Volts (V) Frequency (Hz) Power Cord Length (in.) Plug Type DIMENSIONS & WEIGHT Appliance Dimensions (H x W x D) (in.)	Vacation 19.4 cu. ft. Yes Yes Frost-Free 350 W 15 A 110-120 V 60 Hz 118 120V-3 Prong 83 3/4"** x 35 3/4" x 24"	
CAPACITY Total Capacity (cu. ft.) PERFORMANCE Dedicated Evaporator & Compressor System SuperFreeze® Defrost Process TECHNICAL DETAILS Watts (W) Current (A) Volts (V) Frequency (Hz) Power Cord Length (in.) Plug Type DIMENSIONS & WEIGHT Appliance Dimensions (H x W x D) (in.) Required Cutout Size (H x W x D) (in.)	Vacation 19.4 cu. ft. Yes Yes Frost-Free 350 W 15 A 110-120 V 60 Hz 118 120V-3 Prong 83 3/4"** x 35 3/4" x 24" 84" x 36" x 25"	
CAPACITY Total Capacity (cu. ft.) PERFORMANCE Dedicated Evaporator & Compressor System SuperFreeze® Defrost Process TECHNICAL DETAILS Watts (W) Current (A) Volts (V) Frequency (Hz) Power Cord Length (in.) Plug Type DIMENSIONS & WEIGHT Appliance Dimensions (H x W x D) (in.) Required Cutout Size (H x W x D) (in.) Net / Gross Weight (lbs)	Vacation 19.4 cu. ft. Yes Yes Frost-Free 350 W 15 A 110-120 V 60 Hz 118 120V-3 Prong 83 3/4"** x 35 3/4" x 24" 84" x 36" x 25"	
CAPACITY Total Capacity (cu. ft.) PERFORMANCE Dedicated Evaporator & Compressor System SuperFreeze® Defrost Process TECHNICAL DETAILS Watts (W) Current (A) Volts (V) Frequency (Hz) Power Cord Length (in.) Plug Type DIMENSIONS & WEIGHT Appliance Dimensions (H x W x D) (in.) Required Cutout Size (H x W x D) (in.) Net / Gross Weight (lbs) EFFICIENCY	Vacation 19.4 cu. ft. Yes Yes Frost-Free 350 W 15 A 110-120 V 60 Hz 118 120V-3 Prong 83 3/4"** × 35 3/4" × 24" 84" × 36" × 25" 395 / 437 lbs	

^{*}To verify if you have a refrigeration unit with Soft-Close capability please contact our customer team by calling 1-800-735-4328.

Page 1 of 3 9 / 20

^{**}Height adjustable + / -1/2" (+ / -13 mm)

T36IF905SP

36-INCH BUILT-IN FREEZER COLUMN WITH INTERNAL ICE MAKER




FREEDOM® COLLECTION, PANEL-READY

WARRANTY	
Limited, Entire Appliance, Parts and Labor on Any Part of the Refrigerator that Fails Because of a Manufacturing Defect	2 Year
Limited Warranty for Sealed Refrigeration System*; Parts and Labor	3rd to 6th Year
Limited Warranty for Sealed Refrigeration System*; Parts Only	7th to 12th Year
Limited Warranty for Stainless Steel Rust-Through	Lifetime

^{*}Sealed refrigeration system includes compressor, evaporator, condenser, dryer / strainer and connection tubing

CUTOUT DIMENSIONS




Furniture return

A: Area for installation of power connection.


B: Area for running the water line. It is recommended that the waterbox is placed adjacent to the installation cavity, so that it can be accessed for service without uninstalling the appliance. If this is not possible, place the recessed waterbox adjacent to the water supply socket elevated at the heights as referenced in areas A and B.

C: Niche depth depends on kitchen design. For a flush installation, the depth needs to be at least 24 inches plus the thickness of the door panel.

Stainless steel models contain a panel-ready base unit, ready-to-install stainless steel door(s) with a right or left door swing and handle(s).



TOP VIEW CLEARANCE



** Door handle must be added to this dimension

* Depends on the thickness of the furniture door.

3/4" (19 mm) is relevant for the stainless steel door.
(special Accessory).

3/4" (19 mm)*


Page 2 of 3 9 / 20

T361F905SP 36-INCH BUILT-IN FREEZER COLUMN WITH INTERNAL ICE MAKER



FREEDOM® COLLECTION, PANEL-READY

PRODUCT AND PANEL DIMENSIONS



ACCESSORIES (OPTIONAL)

FLAT STAINLESS STEEL DOOR PANELS

30-Inch Flat Stainless Steel Door Panel Without Dispenser



TFL361R900

For use with Handle

TFL361R905

Handleless

NOTE: Handleless Panels should not be installed on units without the Soft-Close capability. If you are uncertain if you have a refrigeration unit with Soft-Close capability please contact our customer team by calling 1-800-735-4328.

STORAGE



ICEBUCKETL

Large Ice Bucket

FRAMEKIT10

Freedom® Frame Kit

For any custom column installation in 24-inch deep cutouts. With two metal side trims whose placement between the interior cutout wall and the appliance helps overcome the challenge of unfinished cabinet returns.

HANDLES

Choose between two options:

PR36HNDL20

36-Inch Professional Series Handle

or

MS36HNDL20


36-Inch Masterpiece® Series Handle

FILTERS



REPLFLTR55

Freedom® Water Filter Replacement water filter for use in all freezer and bottom freezer models



HEATRKIT20 - 13W @ 120V

Freedom® Heater Kit

When two appliances are installed side-by-side a sealing kit must be used. For combinations that involve a freezer column, this sealing kit is included. For all other (non-traditional, i.e. two wine columns, two bottom freezers, etc.) side-by-side combinations or instances where any appliances are installed less than 6-inches (152 mm) apart from one another but not connected side-by-side, purchase this kit. This kit is recommended for use with any installation in areas that are subject to humidity, or located next to an outside wall.

These warranties give you specific legal rights and you may have other rights that vary from state to state. Limited warranty from date of purchase. For complete warranty details, refer to your Use & Care manual, or ask your dealer.

Specifications are for planning purposes only. Refer to installation instructions and consult your countertop supplier prior to making counter opening. Consult with a heating and ventilation engineer for your specific ventilation requirements. For the most detailed information, refer to installation instructions accompanying product or write to Thermador indicating the model number. Specifications are correct at time of printing. Thermador reserves the right to change product specifications or design without notice. Some models are certified for use in Canada. Thermador is not responsible for products that are transported from the U.S. for use in Canada.

 $1\,800\,735\,4328 \mid USA\,THERMADOR.COM\mid CANADA\,THERMADOR.CA\mid @2020\,BSH\,HOME\,APPLIANCES\,CORPORATION.\,ALL\,RIGHTS\,RESERVED.$

Page 3 of 3 9 / 20