

# INTEGRATED VENTILATION SYSTEM WITH VARIABLE SPEED CONTROL

RNIVS1 | HERITAGE COLLECTION




# FEATURES & BENEFITS


- $\rightarrow$  Variable Blower Controls.
- → Auto ON turns hood on automatically if high temperatures are sensed.
- → LED Lighting provides energy efficiency and a bright cooking area.
- → Removable, Easy-to-Clean Baffle Filters
- Internal Blower included with RNIVS models: 600 CFM
   582 CFM at 0.0" static pressure
- → Designed and Manufactured in California, USA

TECHNICAL INFORMATION		
ELECTRICAL REQUIREMENTS	120VAC/60HZ/15AMP	
METAL HOOD LINERS (HXWXD)		
30" (27"X2"X21")	RNIHL30 & RNIHL36	
36" (33"X2"X21")	RNIHL30 & RNIHL36	
48" (45"X2"X21")	RNIHL30 & RNIHL36	
PRODUCT DIMENSIONS		
APPLIANCE DIMENSIONS (H X W X D) (IN.)	8 7/8" X 20 1/4" X 18 1/2"	
ALL TOLERANCES	± 1/16" ( ± 1.6MM) UNLESS OTHERWISE NOTED	

### CONTROL PANEL









# INTEGRATED VENTILATION SYSTEM WITH VARIABLE SPEED CONTROL

RNIVS2 | HERITAGE COLLECTION



# FEATURES & BENEFITS

- $\rightarrow$  Variable Blower Controls.
- → Auto ON turns hood on automatically if high temperatures are sensed.
- → LED Lighting provides energy efficiency and a bright cooking area.
- → Removable, Easy-to-Clean Baffle Filters.
- → Recommended Accessory with RNIVS2: Transition Duct(ATD10)
- → Internal Blower included with RNIVS models: 1,200 CFM - 1164 CFM at 0.0" static pressure
- ightarrow Designed and Manufactured in California, USA

TECHNICAL INFORMATION		
ELECTRICAL REQUIREMENTS	120VAC/60HZ/15AMP	
METAL HOOD LINERS (HXWXD)		
30" (27"X2"X21")	RNIHL48	
36" (33"X2"X21")	RNIHL48	
48" (45"X2"X21")	RNIHL48	
PRODUCT DIMENSIONS		

# APPLIANCE DIMENSIONS (H X W X D) (IN.) 8 7/8" X 30 1/4" X 18 1/2" ALL TOLERANCES ± 1/16" (± 1.6MM) UNLESS OTHERWISE NOTED

## CONTROL PANEL



