ISLAND

Enjoy unobstructed views of your kitchen with the modern, minimalist lines of the Lux. This sleek hood includes a wireless remote control, and it discreetly mounts into the ceiling above your range or cooktop for power and good

looks combined. Your kitchen will stay clean and smoke free with the Lux's Perimeter Aspiration and multiple blower options, and the tri-level LED light strip ensures a good-looking glow. Available in White and Stainless Steel.






63" Stainless Steel




43" White




Wireless Remote Control



Front\*



Top



\*ALU-E43 has 2 panels, ALU-E63 has 3 panels





MODEL		
Stainless Steel	ALU-E43ASX	ALU-E63ASX
White	ALU-E43AWX	ALU-E63AWX
Size	43"	63"
PERFORMANCE		
Internal Blower (CBI-290A)*	200-290 CFM, 1.4-3 sones	200-290 CFM, 1.4-3 sones
Internal Blower (CBI-600A)*	240-600 CFM, 1.8-6 sones	240-600 CFM, 1.8-6 sones
Internal Blower (PBI-1100A)*	500-1,100 CFM, 3.5-8 sones	500-1,100 CFM, 3.5-8 sones
In-Line Blower (PBN-1000A)*	500-1,000 CFM, sones NA	500-1,000 CFM, sones NA
External Blower (CBE-1000)*	500-1,000 CFM, sones NA	500-1,000 CFM, sones NA
FEATURES		
Controls	Capacitive Touch	Capacitive Touch
Speed Levels	3	3
Auto Delay-Off	Yes	Yes
CleanAir Function**	Yes	Yes
Lighting	LED Strip x 3 (8.5W)	LED Strip x 4 (8.5W)
Tri-Level Lighting	Yes	Yes
Filters	Aluminum Mesh x4	Aluminum Mesh x6
Wireless Remote Control	Yes, RF	Yes, RF
Recirculating***	Yes	Yes
ADA Compliant	Yes	Yes
DUCT SPECIFICATIONS		
Vertical Blower	NA	NA
Horizontal Internal Blower	6"(CBI),10"(PBI)	6"(CBI),10"(PBI)
Horizontal In-Line/External Blower	10"	10"
AC POWER		
Hood w/ CBI-290A	120V, 60Hz, Max. 1.05A	120V, 60Hz, Max. 1.05A
Hood w/ CBI-600A	120V, 60Hz, Max. 3.05A	120V, 60Hz, Max. 3.05A
Hood w/ PBI-1100A	120V, 60Hz, Max. 5.75A	120V, 60Hz, Max. 5.75A
Hood w/ PBN-1000A	120V, 60Hz, Max. 5.75A	120V, 60Hz, Max. 5.75A
Hood w/ CBE-1000	120V, 60Hz, Max. 6.55A	120V, 60Hz, Max. 6.55A
OPTIONAL ACCESSORIES		
Recirculating Kit	ZRC-00LX	ZRC-00LX
Make-Up Air Kit	MUA006A (600 CFM)	MUA006A (600 CFM)
-	MUA008A (1,000 CFM)	MUA008A (1,000 CFM)
	MUA010A (1,100 CFM)	MUA010A (1,100 CFM)
MOUNTING HEIGHT RANGE <sup>†</sup>	36" - 72"	36" - 72"
WARRANTY	1 year parts, 1 year labor	1 year parts, 1 year labor

7.5'

54"

8′

60"

8.5'

66"

9′

72"

MOUNTING HEIGHT<sup>†</sup>

**CEILING HEIGHT** 

6′

36"

6.5'

42"

48"



<sup>\*</sup>Blower sold separately.

\*\*CleanAir turns your hood on once every four hours for 10 minutes on speed one.

\*\*\*Recirculating kit is only compatible with CBI-290A and CBI-600A blowers.

\*Mounting height refers to distance between top of a 36" tall cooking surface and bottom of hood.