# best

### SPECIFICATION SHEET

\*28-3/8", \*34-3/8", \*40-3/8"

Add 1/16"

CERTIFIED

for rivet heads.

# CP34 SERIES RANGE HOODS

All-in-one design includes liner, blower, filtration, controls, lighting, and damper for easy installation into custom canopy hoods. Intended for all residential applications, including commercial-style cooking surfaces.

#### FEATURES

- Cabinet mount custom applications
- Finish: 430 Stainless Steel #4 Brushed
- Widths: 28-3/8," 34-3/8," 40-3/8"
- Depth: 19-1/4"
- 8" round duct connector with backdraft damper
- Two-setting cooktop lighting (Uses two 50W, GU10 halogen lamps. Bulbs included.)
- Easily accessible, dishwasher safe stainless steel baffle filters with handles
- Infinite speed rotary blower control with on-off rocker switch
- Powerful, centrifugal blower with high-efficiency motor produces 290 CFM
- Quiet, normal speed operation
- Heat Sentry<sup>™</sup> automatically turns blower to high speed when excess cooking heat is detected
- For indoor use only

#### SPECIFICATIONS

MODEL NO.	VOLTS	AMPS	CFM / SONES (High Speed)	CFM / SONES (Low Speed)	DUCT
CP34	120	5.0	290 / 11.5	130 / 3.0	8" round

BEST Hartford, Wisconsin www.BestRangeHoods.com 800-558-1711							
REFERENCE	QTY.	REMARKS	Project				
			Location				
			Architect				
			Engineer				
			Contractor				
			Submitted by	Date			

3

\*19<sup>-1/4</sup>

HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to


consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in a state-of-the-art test

laboratory. Sones are a measure of humanly-perceived loudness,

based on laboratory measurements.

To minimize the gap around the power pack, take actual width and depth measurements of power pack and add 1/16" to get **D** and **E** measurements. Cut the hole in the bottom of the cabinet according to dimensions. See chart and illustration for details.

POWER PACK	WIDTH	CUTOUT DIMENSIONS		
MODEL	WIDIN	D	E	
	30"	19%"	28½"	
CP34	36"	19%"	34½"	
	42"	19%"	40½"	



## **CP34 SERIES HOOD SYSTEM**

