

DA 6798 W Shape

Wall ventilation hood

with energy-efficient LED lighting and touch controls for simple operation.



- Headroom – design based on Miele built-in appliances
- Unique user convenience – Con@ctivity
- Powerful – ?? on the booster setting
- Energy-efficient and quiet
- Safe and easy to clean – Miele CleanCover

EAN: 4002516024613 / Material number: 10876860 / Old Material Number: 28679840USA

Construction type	
Wall ventilation hood	•
Operating modes	
Recirculated mode	Convertible
OdorFree charcoal filter (order separately)	DKF25-900
Design	
Color	Obsidian black
Control panel	
Miele@home	•
Electronic controls	•
Touch controls	•
Power levels (number excl. Intensive)	3
Programmable Intensive switch-off	•
Grease filter saturation indicator	•
Programmable grease filter saturation indicator	•
Programmable charcoal filter saturation indicator	•
User convenience	
Run-on time 5/15 min.	•
Cleaning convenience	
Easy-to-clean canopy interior – CleanCover	•
Filter system	
Number of dishwasher safe stainless-steel grease filters (10-ply)	1
Lighting	
LED ClearView lighting	•
Number x W	3 x 3 W
Light intensity in Lx	320 lx
Color temperature in K	3500 Kelvin
Light dimmer function	•
Blower	
Dual-action blower	•
AC motor	•
Extraction	
Air throughput	Values upon request
Safety	
Safety shut-off	•
Single-ply safety glass (ESG)	•
Technical data	
Canopy width in in.(mm)	35 3/8 (898)
Overall min. height for vented and external in in. (mm)	22 3/8 (568)
Overall max. height for vented and external in in. (mm)	22 3/8 (568)
Canopy height in in.(mm)	22 3/8 (568)
Overall min. height for recirculation in in. (mm)	22 3/8 (568)
Canopy depth in in.(mm)	19 1/2 (493)
Overall max. height for recirculation in in. (mm)	22 3/8 (568)
Minimum height above electric hobs in mm	24 1/8 (610)
Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	26 (660)
Net weight in lbs. (kg)	67 (30.0)
Length of electrical wire in ft (m)	2 (0.7)

DA 6798 W Shape

Wall ventilation hood

with energy-efficient LED lighting and touch controls for simple operation.



EAN: 4002516024613 / Material number: 10876860 / Old Material Number: 28679840USA

Standard plug fitted	•
Total connected load in kW	0.35
Fuse rating in A	15
Hard-wired	•
Voltage in V	120
Frequency in Hz	60
Number of phases	1
Installation notes	
Vent connection at top	•
Vent connection at top and rear	•
Diameter of vent connection in in. (mm)	6 (150)
Accessories supplied	
Communication module for Con@ctivity XKM 2000 DA	XKS 3000 Z
Optional accessories	
OdorFree charcoal filter	No
Duct Cover	DADC 6000