### **HERT366GASNET**

# HERITAGE SERIES ALL-GAS RANGE 36" 6 BRASS BURNERS NERO MATT FINISH - COLOR OPTIONS BELOW











Counter-deep maintop for flush installation with kitchen countertops and cabinets

6 Monobloc brass burners with optional cast iron griddle over central segment

Two 19000 BTU power burners with dual ring flame delivering fastest time-to-boil in class

5.9 cu.ft gas oven with dual horizontal convection fans for even baking and roasting on 7 shelf levels

Extra-large high-power infared gas broiler for broiling and grilling

Elegant temperature gauge for control of oven temperature during pre-heating and baking

Smooth-glide telescopic racks

Soft-close oven door with edge-to-edge tempered glass

6 Monobloc brass burners
2 power burners 1300 - 19000 BTU 1 large burner 2500 - 10400 BTU 2 medium burners 1500 - 5900 BTU 1 simmer burner 750 - 3500 BTU
Solid metal
Electric with thermocouple safety device
Cast iron
1" stainless steel island trim Wok ring Simmer ring
Gas oven with infrared gas broiler
Bake element 4100-17000 BTU Broiler element 11000 BTU
5.9 cu.ft
Dual horizontal fans
Bake - Convection Bake - Broil
Tempered edge-to-edge triple glass
Soft-close
2 sets of telescopic glides 2 shelves Baking tray with grill trivet
IONS
120V 60 Hz - 300W 2.5 Amp dedicated circuit
NEMA 5-15P plug with 59" cord
CSA

for Heritage Series
egs covers - set of 2
griddle
lescopic glides for oven rack
ni white porcelain baking dish
)

Bertazzoni ranges are available in NG

(standard) or LPG (selected models). A gas

conversion kit is included with every range.



**HERT366GGASXT** Stainless steel finish




Gas type and conversion


HERT366GGASAVT Ivory gloss finish


## **HERT366GASNET**


## HERITAGE SERIES ALL-GAS RANGE 36" 6 BRASS BURNERS NERO MATT FINISH











38"5/8

#### **Side Clearance Requirements:**

6" min clearance from edge of maintop.

Overhead Cabinet:18" min height above countertop

13" max depth.

#### **Ventilation Hood Clearance:**

Ventilation Hood Clearance: recommended height 25 ½" – 31 ½" above cooking surface.


### **ELECTRICAL LINE**


A properly-grounded horizontally- mounted electrical receptacle should be installed no higher than 3" (7.6 cm) above the floor, no less than 2" (5 cm) and no more than 8" (20,3 cm) from the left side (facing product). Check all local code requirements.


#### **GAS LINE**


An agency-approved, properly-sized manual shut-off valve should be installed no higher than 3" (7 .6 cm) above the floor and no less than 2" (5 cm) and no more than 8" (20.3 cm) from the right side (facing product).

To connect gas between shut-off valve and regulator, use agency-approved, properly sized flexible or rigid pipe. Check all local code requirements.











Disclaimer: while every effort has been made to insure the accuracy of the information contained in this document, Fratelli Bertazzoni reserves the right to change any part of the information at any time without notice. For detailed installation specifications consult the installation manual. Fratelli Bertazzoni, Bertazzoni and the winged wheel brand icon are registered trademarks of Bertazzoni Spa.