



Product: 30 Inch Wall Mount Range Hood

Model Number: HRH3007

BLOWER RATING

BLOWER RATINGS	CFM	SONES (DB)
Low	300 CFM	56
Medium	420 CFM	63
High	600 CFM	64

PRODUCT DIMENSIONS

Range Hood Size (in)	30
Product Width (in)	30
Product Depth (in)	19
Product Height (in)	11 7/8" (w/out duct covers) 45 1/2" (including duct covers)
Duct size (in)	Diameter: 6
Duct Shape	Round
Gross Weight (lb.)	38.4
Net Weight (lb.)	28.3



FEATURES & BENEFITS

- + **Multiple Fan Speeds** - 3 fan speeds allow for easy adjustment between high, medium and low suction
- + **LED Lighting** - Two 3.5-watt LED lights to illuminate your cooking area and save energy
- + **Quiet 60dB Operation** - Quiet operation keeps noise level at a maximum 60 decibels
- + **Convertible** - Vent out or recirculating (ductless) option with carbon filters (not included)
- + **Commercial-style Baffle Filter** - Large, commercial-style 430 grade stainless steel baffle filter maximizes air flow and grease filtering while the hood is in operation
- + **Touch Control with Digital Display** - Features touch control with integrated backlit digital display that shows clock and a reminder to clean filters
- + **600 CFM of Suction** - 600 CFM of suction effectively removes odors, smoke, grease and moisture from your cooking area
- + **Stainless Steel Finish** - Stainless steel finish offers modern design aesthetic and is built to withstand high heat, grease, oil and steam
- + **Remote Control** - Remote control allows for adjusting fan speed and lighting from anywhere in the kitchen
- + **Duct Cover Included:** The stainless steel duct cover matches the linear styling of the THOR kitchen professional 30 Inch vent hood and extends the height of the hood for 9 foot ceilings

TECHNICAL DETAILS

Lighting	LED light x 2
Noise level (Max.)	67 dB
Power	120V
Frequency	60HZ
Amperage	5A
Filter type	430SS Baffle filter
Blower type	Internal
Control type	Button, no auto shut off No delayed shut off
Accessories	RHDC07 (hood duct cover) - sold separately
Fan Speeds	2000r/min
Color/Finish	Stainless steel

WARRANTY: ONE YEAR LIMITED WARRANTY



INSTALLATION & SPEC

INSTALLTION DRILLING AND LINING

1. Draw a vertical line on the supporting wall up to the ceiling, or as high as practical, at the centre of the area in which the hood will be installed.
2. Draw a horizontal line 28-30 inches above an electric top or 30-32 inches above a gas top.
3. Place chimney mounting brackets on the wall as shown about 1" (27mm) from the ceiling or upper limit aligning the centre (notch) with the vertical reference line.

