



The Legacy Companies
 3355 Enterprise Avenue, Suite 160, Fort Lauderdale, FL 33331
 Sales: (954) 202-7419 • Sales@TheLegacyCompanies.com
 Tech Service: (877) 368-2797 • Service@MaxxHelp.com

Project Name: _____

Location: _____

Item #: _____ Qty: _____

Model: _____

www.MaximumFoodService.com

SELF CONTAINED PREMIUM OUTDOOR ICE MAKER

Model: MIM50P-O

International Model: Add -50 (220V/50Hz/1Ph)
 or -60 (220V/60Hz/1Ph)



The MIM50P-O Premium Compact Outdoor Ice Maker comes with a drain pump, metal ice scoop and produces up to 65 lbs of slab cubed ice per day. It also includes a self-contained 25 pound storage bin and an internal blue LED light that turns on when the door opens. Suitable for freestanding or built in applications, the stainless steel outer cabinet with stainless door looks good in any setting. The MIM50P-O runs on standard household electrical current. UL approved for commercial use.

ICE PRODUCTION

Air Temp 70°F (21°C) Water Temp 50°F (10°C)
 Daily Ice Production: 65 lbs (23kg)
 Energy Consumption 10.1kWh/100lb of ice produced
 Water Usage 13.8 gal./100lb of ice produced

Air Temp 90°F (32°C) Water Temp 70°F (21°C)
 Daily Ice Production: 51 lbs (31kg)

Storage Bin holds 25lbs of ice with automatic overflow prevention
 Gravity Drain connection is required, along with a water supply line.

OPERATING REQUIREMENTS

Ambient Temperature Range 50° to 99°F (10° to 37°C)
 Water Temperature Range 40° to 90°F (4° to 32°C)
 Water Supply Line Connection 1/4" O.D. Compression
 Water Pressure Range
 Min PSI 15 Max PSI 75 (above 75 requires a regulator)
 Min Bar 1.0 Max Bar 5.5

FEATURES and CONSTRUCTION


- Exterior Material: Stainless Steel
- Air Cooled Compressor
- Drain Pump
- Adjustable, sturdy plastic legs
- Internal blue LED light when door is open
- Built-In Self Cleaning Mode for use with nickel safe cleaning solution
- Includes: Stainless Steel Scoop & Built-in Scoop Holder
 Tubing for Supply and Drain Lines
 NEMA 5-15 cord set for simple installation
- * A Water filter is recommended for a more efficient operation with less required maintenance and cleaning.
- * 3rd Party Approvals: ANSI NSF 12, ANSI UL 563 & DOE2017

REFRIGERANT

- CFC & HCFC free R-134A

ELECTRIC

120V/60Hz/1 Ph (NEMA 5-15P)
 (220V/50Hz/1ph available as an option)



Certified to
ANSI-NSF 12



Certified to
ANSI UL 563



Maxx Ice WARRANTY (USA / CANADA)

One (1) year parts
 One (1) year on-site labor
 Five (5) years compressor (part only)
 Administered by The Legacy Companies, 877.368.2797

Due to periodic changes in designs, methods, procedures, policies and regulations, the specifications contained in this sheet are subject to change without notice. While we exercise good faith efforts to provide information that is accurate, we are not responsible for errors or omissions in information provided or conclusions reached as a result of using the specifications. By using the information provided, the user assumes all risks in connection with such use.

The built in performance enhancing functions ensure that given proper attention and preventative maintenance, each Maxx Product will deliver years of trouble free, reliable, low maintenance, efficient operation.




The Legacy Companies
 3355 Enterprise Avenue, Suite 160, Fort Lauderdale, FL 33331
 Sales: (954) 202-7419 • Sales@TheLegacyCompanies.com
 Tech Service: (877) 368-2797 • Service@MaxxHelp.com

Project Name: _____
 Location: _____
 Item #: _____ Qty: _____
 Model: _____

www.MaximumFoodService.com

SELF CONTAINED PREMIUM OUTDOOR ICE MAKER



MIM50P-O	
In: External Dimensions W x D X H	14.6 x 23.4 x 32.6
mm: External Dimensions W x D X H	370 x 593 x 828
Average Amp Draw	1.9
Unit Weight	92 lb / 41.7 kg
Shipping Weight	101 lb / 45.8 kg
Production based on ambient conditions	
50°F Water / 70°F Air	Up to 65 lbs of ice/day
70°F Water / 90°F Air	Up to 51 lbs of ice/day
Ice Cube Produced (Dimensions)	Clear Slab Cube (3/4 x 3/4 x 1" / 19 x 19 x 25mm)

Due to periodic changes in designs, methods, procedures, policies and regulations, the specifications contained in this sheet are subject to change without notice. While we exercise good faith efforts to provide information that is accurate, we are not responsible for errors or omissions in information provided or conclusions reached as a result of using the specifications. By using the information provided, the user assumes all risks in connection with such use.