DOB30M977S

30-INCH SINGLE WALL OVEN

MODERNIST COLLECTION



Coming Soon

AVAILABLE MODELS

- DOB30M977SM 30" Steam-Assisted Single Wall Oven Graphite Stainless Steel
- DOB30M977SS 30" Steam-Assisted Single Wall Oven -Stainless Steel

FEATURES & BENEFITS

- Available in graphite stainless steel and silver stainless steel.
- Exclusive Four-Part Dual Pure Convection heat, air, baffle and filter to precisely distribute heat for superior cooking results.
- Steam and Convection Oven the power of steam assist and convection cooking in one.
- Oven capacity: 4.8 cu. ft.
- Easy to use / refill water reservoir for steam cooking.
- 7" LCD control panel.
- BrightVue[™] integrated LED lights in the oven door + Halogen lights.
- SoftShut™ oven doors.
- Dacor iQ Kitchen app with integrated Wi-Fi to control and monitor remotely.

| ACCESSORIES (Included) | |
|---------------------------|---|
| GlideRack™ | 2 |
| Standard Rack | 1 |
| Temperature Probe | 1 |
| Mesh Filter | 2 |
| Automatic Water Reservoir | 1 |

| ACCESSORIES (Optional) | SKU |
|--------------------------|---------|
| Cookie Sheets (set of 3) | ACSM303 |

GENERAL PROPERTIES Cooking Modes Bake - Broil - Convection Bake - Convection Roast - Convection Broil - Four Part Pure Convection - Pure Convection Sear - Steam Bake - Steam Roast Additional Features Cleaning Type Self Clean GreenClean™ Controls 7" TFT LCD Wi Fi Yes Rack Positions 6

| | GreenClean™ | |
|--|-------------------------------------|--|
| Controls | 7" TFT LCD | |
| Wi Fi | Yes | |
| Rack Positions | 6 | |
| Convection Type | Dual Convection with Mesh Filter | |
| Lighting | BrightVue™ - LED + Halogen | |
| OVEN PERFORMANCE | | |
| Bake | 3,000W - 8 pass | |
| Broil | 4,400W - 10 pass | |
| Control Features | | |
| Delay Start | Yes | |
| Kitchen Timer | Yes | |
| Sabbath Mode | Yes | |
| Child Lock | Yes | |
| Additional Modes | | |
| Keep Warm | Yes | |
| Proof (lower temp) | Yes | |
| Proof | Yes | |
| Pizza Stone Mode | Yes | |
| Dehydrate | Yes | |
| Gourmet Cook | Yes | |
| InstantHeat™ | Yes | |
| Temperature Probe | Yes | |
| Auto Conversion | Yes | |
| TECHNICAL DETAILS | | |
| Circuit Breaker (A) | 30 | |
| Volts (V) | 240 / 208 | |
| Frequency (Hz) | 60 | |
| Energy Source | Electric | |
| DIMENSIONS & WEIGHT | | |
| Appliance Dimensions (H x W x D) (in.) | 28 1/2" x 29 2/5" x 24 2/5" | |
| Required Cutout Size (H x W x D) (in.) | 27 1/4" x 28 1/2" x 23 1/2" | |
| Oven Capacity (cubic feet) | 4.8 | |
| Net Weight (lbs) | 97 | |
| WARRANTY | | |
| Limited, Parts and Labor | 1 Year | |


DOB30M977S

30-INCH SINGLE WALL OVEN


MODERNIST COLLECTION



APPLIANCE DIMENSIONS




INSTALLATION UNDERCOUNTER STANDARD DIMENSIONS



- 01 Gas or electric cooktops may be installed ove rthis oven. See cooktop installation instructions for cutout size. See label on top of approved cooktop models.
- **02** Gas and Electrical connections for Gas Cooktop must be located in an adjacent accessible location to the right.

INSTALLATION WALL MOUNT DIMENSIONS



- **01** Junction Box
- **02** Allow a minimum of 22" for clearance to adjacent corners, drawers, walls, etc. when door is open.

| APPLIANCE DIMENSIONS | | |
|----------------------|---------------------|--|
| А | 28 4/5" (73.1cm) | Overall height (Recessed height in Flush install) |
| В | 28 1/2" (72.4cm) | Recessed width |
| С | 27 1/5" (69.1cm) | Recessed height |
| D-1 | 23 1/8" (58.7cm) | Recessed depth (Standard install) |
| D-2 | 24 2/5" (62.0cm) | Recessed depth (Flush install) |
| Е | 29 3/4" (75.6cm) | Door width |
| F | 47 1/4" (120cm) | Conduit length |
| G | 30" (76.2cm) | Overall width (Handle width) |
| Н | 2 1/5" (5.6cm) | Handle depth |

| CABINET | STANDARD DIMENSIONS |
|---------|--|
| А | Min. 11/16" (1.75cm) - Overlap of over side edges of cutout |
| В | Min. 1 3/8" (3.5cm) |
| С | 4" (10.1cm) |
| D | Min. 28 1/2" / Max. 28 5/8" (Min. 72.4cm / Max. 72.7cm) |
| E | Min. 1" / Max. 1 1/4" (Min. 2.5cm / Max. 3.2cm) |
| F | Min. 27 1/4" / Max. 27 3/8" (Min. 69.2cm / Max. 69.5cm) |
| G | 24" (61cm) |
| Н | Min. 22" (Min. 55.9cm) |
| I | Max. 9 1/2" (Max. 24.1cm) - Junction Box |
| J | 36" (91.4cm) - Counter top height |
| K | 25" (63.5cm) |

| CABINET | STANDARD DIMENSIONS |
|---------|--|
| А | Min. 28 1/2" / Max. 28 5/8" (Min. 72.4cm / Max. 72.7cm) |
| В | Min. 1 3/8" (3.5cm) |
| С | Min. 31" (Min. 78.7cm) |
| D | Min. 28 1/2" / Max. 28 5/8" (Min. 72.4cm / Max. 72.7cm) |
| Е | Min. 1" / Max. 1 1/4" (Min. 2.5cm / Max. 3.2cm) |
| F | Min. 27 1/4" / Max. 27 3/8" (Min. 69.2cm / Max. 69.5cm) |
| G | 23 1/2" (59.7cm) |
| Н | Min. 22" (Min. 55.9cm) |
| I | Max. 9 1/2" (Max. 24.1cm) - Junction Box |
| J | Min. 11/16" (1.75cm) - Wooden cabinet thickness |


DOB30M977S

30-INCH SINGLE WALL OVEN

MODERNIST COLLECTION




INSTALLATION UNDERCOUNTER CUTOUT DIMENSIONS



- 01 Gas or electric cooktops may be installed ove rthis oven. See cooktop installation instructions for cutout size. See label on top of approved cooktop models.
- **02** Gas and Electrical connections for Gas Cooktop must be located in an adjacent accessible location to the right.

INSTALLATION WALL CABINET CUTOUT DIMENSIONS



- **01** Junction Box
- **02** Allow a minimum of 22" for clearance to adjacent corners, drawers, walls, etc. when door is open.

| CABINET | DIMENSION |
|---------|---|
| А | Min. 1 3/8" (3.5cm) |
| В | 4" (10.1cm) |
| С | Min. 30 1/5" / Max. 30 3/10" (Min. 76.7cm / Max. 76.9cm) |
| D | Min. 1" / Max. 1 1/4" (Min. 2.5cm / Max. 3.2cm) |
| E | Min. 29" / Max. 29 1/8" (Min. 73.7cm / Max. 74.0cm) |
| F | 24 4/5" (63cm) |
| G | Min. 22" (Min. 55.9cm) |
| Н | Max. 9 1/2" (Max. 24.1cm) - Junction Box |
| I | 36" (91.4cm) - Counter top height |
| J | 25 4/5" (65.5cm) |

| CABINET | FLUSH INSTALL DIMENSION |
|---------|---|
| А | Min. 30 1/5" / Max. 30 3/10" (Min. 76.7cm / Max. 76.9cm) |
| В | Min. 1 3/8" (3.5cm) |
| С | Min. 31" (Min. 78.7cm) |
| D | Min. 30 1/5" / Max. 30 3/10" (Min. 76.7cm / Max. 76.9cm) |
| E | Min. 1" / Max. 1 1/4" (Min. 2.5cm / Max. 3.2cm) |
| F | Min. 29" / Max. 29 1/8" (Min. 73.7cm / Max. 74.0cm) |
| G | 24 4/5" (61cm) |
| Н | Min. 22" (Min. 55.9cm) |
| ı | Max. 9 1/2" (Max. 24.1cm) - Junction Box |
| J | Min. 11/16" (1.75cm) - Wooden cabinet thickness |