

700 Series 30" Self Cleaning Single Wall Oven

F7SP30W1



Series			700
Type Size Colour			PYRO 30"x30" WHITE
Stainless Steel Aestethics Oven Type Temperature Regulation			Embossed window profile with bended edges Multifunction 2 Fans (True Euro Convection) Full Electronic
Key	Functions		Tun Electronic
LIGHT	LIGHT		•
DEHIDR	DEFROST		•
	DEHYDRATE	.::.]	•
KEEP WARM	WARM		•
	WARM +	<u>[_555</u>]	•
BAKE CONV.	BAKE		•
	ROAST		•
	TRUE CONVECTION BAKE		•
	CONVECTION ROAST	$[\overline{oldsymbol{arkappa}}]$	•
	CONVECTION BAKE	[<u>*</u>]	•
	CONVECTION GRILL	$[\underbrace{oldsymbol{lpha}}_{oldsymbol{lpha}}]$	•
	CONVECTION BROIL	$\left[\widetilde{m{st}} ight]$	•
PIZZA	PIZZA	<u>[@]</u>	•
BROIL	BROIL LEVELS	[**]	•
SELF C.	SELF CLEAN	[:::]	•
Control	Panel		
Control typ	ре		MODULAR - Electronic
Display Many Basines			TFT 3,5"
Menu Recipes Commands			Full Touch
Language			11
Special	Features		
Demo Mo			•
Brightness setting (ON condition)			•
Brightness setting (OFF condition)			•
Beeper volume setting			•
Date form	at Fast Preheat		•
	ZZA function 310°C		•
Child Doo			•

FULGOR

MILANO

Commands Lock	•			
Sabbath mode	•			
12/24 hours clock format	•			
°C/°F degree unit	•			
Door miscro switch	•			
Event logs (for Service)	•			
Oven Door(s)				
Oven Glass Window	Large See Through Glass			
Door Cooling System	4 Pane Heat Resistant Glass			
Door Hinges	Heavy Duty Steady Tilt			
Oven Cavity				
Gross Capacity (cbft)	4.4			
Net Capacity (cbft)	4.1			
Cavity Enameling Colour	Black			
Rack Positions	6			
Oven Lights	3 or 2 x 20W Halogen			
Broil Upper Heating Element	3500 W (240V)			
Upper Auxiliary Element Wattage	1032W (240V)			
Concealed Bake Lower Heating Element	3000 W (240V)			
Convection Element Wattage	2x1300W (240V)			
Oven Accessories				
Chromed racks	•			
Enameled Grill set (basin + anti splash)	•			
Telescopic chromed rack	•			
Meat probe	•			
Dimensions/Weight - (In or Lbs)				
Overall dim - width	29 11/16" (754mm)			
Overall dim - height	27-7/8" (707mm)			
Overall dim - depth	24" (610mm)			
Cutout - width	28 7/16" (722mm)			
Cutout - height (min)	27-1/4" (692mm)			
Cutout - depth (min)	23-1/4" (590mm)			
Power / Ratings (208/240 V, 60 Hz)				
KW/Amps rating at 240V, 60Hz	3.70kW - 15.4A			
KW/Amps rating at 208V, 60Hz	3.50kW - 16.8A			
Cable + Conduit	•			
INSTRUCTIONS FOR USE				
Use & Care Manual	EN, SP, FR			
Installation Manual	EN, SP, FR			
	, ,			