



Features and Benefits

Performance

- 450 Watt Heating Element Concealed Below Drawer
- Special Dough Proofing Mode

Convenience

- . Sturdy Ball Bearing Telescopic Rails for Smooth Opening
- Star-K certified
- 1 Hour Automatic Shut-Off Function with Adjustable Timer

Capacity

- 1.9 Cu.Ft. Large Cavity
- Lower Side Walls Allow Easy Loading and Unloading of Drawer


Notes: All height, width and depth dimensions are shown in inches. *Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be foundin a ccompanying product literature or you may contact your account manager for further details.

For more information on our entire line of products, go to boschappliances.com or call 1-800-944-2904.

Copyright ©2014 BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.


Litho Date: 03/2014





* Power cord on warming drawer is 84" (2134 mm)

measurements in inches (mm)



Flush Install Top View	Side View
3/4" (19) 3/4" (19) reveal reveal cleats cleats -25 ¹ /2" (648) -27" (686)	reveal cleats (25) 93/4" (248) (248
	measurements in inches (mm)

Features	
Power output heating	0.450
Power Level	high, low, medium
Type of control	illuminated,
	TouchControl Basic
Temperature control	electronic
Time control	electronic
Technical Specification	

rechnical Specification	
UPC code	825225908715
Product color	Stainless steel
Alternative colors available	
Watts (W)	450
Current (A)	15
Volts (V)	120
Frequency (Hz)	60
Approval certificates	CSA
Power Cord Length	84"
Plug type	120V-3 prong
Required cutout size (HxWxD) (in)	9 1/4" x 25 1/2" x 23 1/2"
Overall appliance dimensions (HxWxD) (in)	9 5/8" x 26 3/4" x 22"
Product packaging dimensions (HxWxD) (in)	14 1/2" x 35
	5/8" x 30 1/2"
Net weight (lbs)	56
Gross weight (lbs)	62

Notes: All height, width and depth dimensions are shown in inches. *Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be foundin a ccompanying product literature or you may contact your account manager for further details.