




MODEL: AEL361DF

36" ELISE DUAL FUEL RANGE







NEW! ANTIQUE BRASS HANDLE STANCHION & ANTIQUE BRASS KNOB OPTION

The AGA Elise can now be further customized with stately Antique Brass Handle Stanchions and Antique Brass Knobs that highlight the refined elegance of the range. Note: Antique Brass Handle Stanchion and Knobs option must be specified at time of ordering.

In the re-imagining of the classic Elise design, AGA took its cues from the modern farmhouse movement itself. Rustic yet refined, the Elise blends old and new in masterful ways, both fresh and timeless, with just a hint of the exquisite.

Complimented by stunning new cruciform knobs with knurling, shipped standard in Brushed Nickel, but also available as after-market options in four additional versatile hardware finishes (Polished Chrome, Polished Brass, Polished Copper, Brushed Brass and Black Anodized Aluminum), the re-imagined AGA Elise confidently steps into the spotlight along side its classic AGA siblings.



SPECIFICATIONS

- Product Dimensions: 35 1/2" W x 27 5/8" D x 36 9/16" H
- · Shipping weight (lbs): 390lbs (includes range, crate & pallet)

WARRANTY

· 2 Year Warranty on parts and labor with exception of cosmetic damage

FINISHES

NOTE: Colors not in stock could have a 4-12 week lead time (check for availability).

Ranges manufactured using Soho colors are only available with stainless steel fascia.

CLASSIC COLOR COLLECTION













36" ELISE DUAL FUEL RANGE

Total Ovon Canacity	4.5 cu. ft.	
Total Oven Capacity		
Usable Oven Space	28" W x 14" D x 14 ½" H	
Cooking Mode	Multi-function Oven with 7 Cooking Modes	
Cleaning Type	EasyClean™ Enamel	
Controls	Knobs on fascia	
Sealed Burners	Yes	
Cooktop Performance		
Cooktop Dimensions	35 ½" W x 21 ¾" D	
Number of Brass Burners	5	
Power of Left Front Burner	12,000 BTU High; 2,400 BTU Low	
Power of Back Left Burner BTU	12,000 BTU High; 2,400 BTU Low	
Power of Center Burner BTU	17,000 BTU High; 3,400 BTU Low	
Power of Front Right Burner BTU	6,000 BTU High; 1,200 BTU Low	
Power of Back Right Burner BTU	12,000 BTU High; 2,400 BTU Low	
Electrical Details		
Circuit Breaker (A)	40A	
Volts (V)	240V	
Frequency (Hz)	60Hz	
Plug Type	4-prong NEMA 14-50P	
Power Cord Length	50"	
Energy Source	Electric Oven and Gas Cooktop	
Gas Type	Natural Gas with LP Conversion Kit included	
Alternative Gas Type	Liquid Propane	
Dimensions & Weights		
Appliance Dimensions	35 ½" W x 27 5/8" D x 36 5/16" H	
Depth with Door Open	44 5/16"	
Weight	306 lbs.	
Shipping Weight	390 lbs.	
Package Dimensions	49 1/4" W x 31" D x 46 1/2" H	
Accessories Included		
2 x Telescopic rack with runners 1 pastry tray 4 grates with burner heads	Toe kick, Anti-tip device, Handra 1 LP Conversion Kit	

OVEN FEATURES

- · Multifunction oven with 7 settings including true European dual-convection cooking, fan-assisted baking, browning, thaw & serve, convection broiling, warming and conventional cooking
 - · Large 4.5 cu. ft. oven
 - · Two robust telescopic glide-out racks
 - · Dual broiler system
 - Includes cookware accessories
 - · One Pastry Tray

COOKTOP FEATURES

- · 5 sealed brass burners provide for easy clean-up and prevent messy spills from reaching the oven or internal components
 - · Powerful 17,000 BTU center burner is ideal for rapid boiling, wok cooking and large pots
 - · Three 12.000 BTU burners
 - · One 6,000 BTU burner can be turned down to a low 1.200 BTU simmer
 - · Each burner is equipped with thermocouple safety mechanism
- · Continuous cast iron cooktop to smoothly slide cookware across burners without spillage
 - · Locking mechanism secures grates in place during cooking
 - · Grates are easy to remove for cleaning
 - · Matte finish cast iron grates are easy to clean and won't discolor
- · Stunning new cruciform knobs with knurling, available in a selection of versatile hardware finishes
- · Convenient storage drawer stores cookware and even oven racks







36" ELISE DUAL FUEL RANGE

Installation Clearance Dimensions	
A - Gap between side of appliance and adjacent vertical surface ABOVE cooktop level	4 1/2"
B - Gap between side of appliance and adjacent vertical surface BELOW cooktop level	³ / ₁₆ " (U.S.) ¹ / ₂ " (Canada)
C - Gap between cooktop level and any horizontal combustible surface	31 1/2 "
D - Maximum depth of cabinets installed above the top surface cooking sections	13 "
E - Minimum distance between horizontal surfaces less than dimension C	35 ½" (U.S.) 36 ¾" (Canada)
F - Minmum distance between horizontal cabinets and worktop surfaces adjacent to range	18"

