


	INTERNAL BLOWER STANDARD	INTERNAL BLOWER with ACT™ AIRFLOW CONTROL TECHNOLOGY™*		
SINGLE BLOWER (INCLUDED) Min. - Max. CFM	200 - 750	200 - 590	200 - 390	200 - 290
SINGLE BLOWER (INCLUDED) Min. - Max. Sones	0.5 - 7	*AIRFLOW CONTROL TECHNOLOGY™ (ACT™) is an exclusive feature built into specific Zephyr hoods which can limit the maximum blower CFM to meet local code requirements.		
DUAL BLOWER (OPTIONAL) Min. - Max. CFM	350 - 1,300			
DUAL BLOWER (OPTIONAL) Min. - Max. Sones	1 - 8			




ACT™ POWERWAVE™




Optional Wireless Remote Control



FRONT



SIDE



BACK

MODEL

Stainless Steel
SizeZRP-E36BS
36"ZRP-E48BS
48"

BLOWER PERFORMANCE

Included Single Blower

200-750 CFM, 0.5-7 Sones

200-750 CFM, 0.5-7 Sones

ACT 590*

200-590 CFM

200-590 CFM

ACT 390*

200-390 CFM

200-390 CFM

ACT 290*

200-290 CFM

200-290 CFM

Optional Dual Blower

350-1,300 CFM, 1-8 Sones

350-1,300 CFM, 1-8 Sones

FEATURES

ACT™ Technology

590, 390, 290, Single Blower Only

590, 390, 290, Single Blower Only

Controls

Electronic LCD

Electronic LCD

Speed Levels

6**

6**

Auto Delay-Off

Yes

Yes

CleanAir Function

Yes

Yes

Directional Lighting

LumiLight LED, 6W x2

LumiLight LED, 6W x4

Dual-Level Lighting

Yes

Yes

Filters

Pro Baffle x2

Pro Baffle x3

Grease Collection Tray

Yes

Yes

Wireless Remote Control

Yes, Optional

Yes, Optional

Recirculating Option

No

No

Duct Cover Extension Option

Yes

Yes

ADA Compliant

Yes (w/ remote accessory)

Yes (w/ remote accessory)

DUCT SPECIFICATIONS

Vertical Single Internal Blower

8" Round

8" Round

Horizontal Single Internal Blower

NA

NA

Vertical Dual Internal Blower

10" Round

10" Round

Horizontal Dual Internal Blower

NA

NA

AC POWER (Single Blower)

120V, 60Hz at Max. 5A

120V, 60Hz at Max. 5A

AC POWER (Dual Blower)

120V, 60Hz at Max. 8A

120V, 60Hz at Max. 8A

OPTIONAL ACCESSORIES

Wireless Remote Control

14000005

14000005

Dual Internal Blower

PBD-1300B

PBD-1300B

Duct Cover Extension

Z1C-00RP

Z1C-00RP

Stainless Steel Telescopic Backsplash

AK1716

AK1718

Make-Up Air Kit (Single Blower)

MUA008A

MUA008A

Make-Up Air Kit (Dual Blower)

MUA010A

MUA010A

MOUNTING HEIGHT RANGE***

24" - 36"

24" - 36"

WARRANTY

3 years parts, 1 year labor

3 years parts, 1 year labor

CEILING HEIGHT

8'

8.5'

9'

9.5'

10'

10.5'

11'

12'

STANDARD
DUCT COVER

Ducted Mounting Height***

24" - 28.5"

24" - 34.5"

24" - 36"

27" - 36"

33" - 36"

NA

NA

NA

DUCT COVER
EXTENSION

Ducted Mounting Height***

NA

NA

24" - 29"

24" - 35"

24" - 36"

24" - 36"

24" - 36"

29" - 36"

*ACT™ only available with single internal blower.

**When ACT™ is enabled the number of fan speeds will be reduced to maximum 3 speeds.

***Mounting height refers to distance between top of a 36" tall cooking surface and bottom of hood.

ACT™

Airflow Control Technology™ (ACT™)

is an exclusive feature built into specific Zephyr hoods which can limit the maximum blower CFM to meet local code requirements.

POWERWAVE™

PowerWave™ 3-Phase Blower Technology

delivers best-in-class performance with unparalleled quiet operation. It provides more power while minimizing noise and improving efficiency. Plus, its 1,300 CFM blower option makes it the most powerful dual-internal blower on the market.

Specifications subject to change, check zephyronline.com for up-to-date information.
Zephyr Ventilation | 2277 Harbor Bay Parkway, Alameda, CA 94502 | 888.880.VENT

MAY22.0101

